

- C. All pits will be fenced with normal fencing material to prevent live-stock from entering the area.
- D. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or separate disposal application will be submitted to the USGS for approval.
- E. Oil produced during operations will be stored in tanks until sold.
- F. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- G. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
- H. All trash and debris will be buried or removed from the wellsite within 30 days after drilling and/or completion operations have been finished.

8. ANCILLARY FACILITIES - None required.

9. WELLSITE LAYOUT

- A. Exhibit VI shows the relative location and dimensions of the well pad, reserve pits, and major rig components.
- B. Only minor leveling will be required to construct the location. The ground surface at the wellsite is relatively level, with only minor undulations and a gradual downward slope from west to east. It is estimated that a cut of approximately 2' will be necessary in the west portion of the drilling pad area. The access road route is also comparatively level, with only minor undulations in the surface. The road and pad surface will be covered with 6 inches of compacted caliche.
- C. The reserve pits will be plastic-lined.
- D. The pad and pit area has been staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE

- A. After drilling and/or completion operations have been finished, all equipment and other materials not needed for further operations will be removed. Pits will be filled and the location cleaned of all trash and junk, so as to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Any unguarded pits containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the BLM and the USGS will be complied and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.