N.M.O.C.D. COPY

RECEIVED

NOV 6 1979

## United States Department of the Interior

GEOLOGICAL SURVEY

P. O. Drawer U Artesia, New Mexico 88210 O. C. C.

ARTESIA, OFFICE

November 2, 1979

Mesa Petroleum Company 1000 Vaughn Building Midland, Texas 79701

Gentlemen:

MESA PETROLEUM COMPANY Derrick Federal Com No. 1 2160 FNL 1980 FWL Sec. 5 T.16S R.28E Eddy County Lease No. NM 33277

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 9,600 feet to test the Morrow is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

- 1. Drilling operations authorized are subject to compliance with the attached General Requirements for Oil and Gas Operations on Federal Leases, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the Surface Use Plan and these Conditions of Approval including the attached General Requirements.
- 3. Submit a Daily Report of Operations from spud date until the well is completed and the Well Completion Report (form 9-330) is filed. The report should not be less than 8" x 5" in size and each page should identify the well.
- 4. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Guidelines. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318).
- 5. Before drilling below the 8-5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
- 6. A kelly cock will be installed and maintained in operable condition.

