

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Lepas oil & Gas Corp.</i>		Lease <i>Duffield St. Con.</i>		Well # <i>1</i>	
Location of Well	Unit <i>B</i> <i>660N 1940E</i>	Section <i>32</i>	Township <i>18</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor	<i>Delta Drilling Co.</i>		Type of Equipment <i>Rotary to start 11-30-79</i>		
<i>* witness Class H Cement as per C-101</i> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>16"</i>	<i>11 3/4"</i>	<i>42</i>		<i>350</i>	<i>400 cu.</i>
<i>11"</i>	<i>8 7/8"</i>	<i>24</i>		<i>2800</i>	<i>1000 cu.</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>11.6</i>		<i>9000</i>	<i>500</i>
Casing Data:					
Surface _____ joints of <i>8 7/8</i> inch <i>24</i> # Grade <i>J-55</i>					
(Approved) (Rejected) _____					
Inspected by <i>M.S.</i> date <i>12/5/79</i>					
Cementing Program					
Size of hole <i>12 1/4</i> Size of Casing <i>8 7/8</i> Sacks cement required _____					
Type of Shoe used <i>guide</i> Float collar used <i>none</i> Btm 3 jts welded <i>yes</i>					
TD of hole <i>1800</i> Set <i>1800</i> Feet of <i>8 7/8</i> Inch <i>24</i> # Grade <i>J-55</i>					
New-used csg. @ <i>1800</i> with <i>20</i> sacks neat cement around shoe					
+ <i>520</i> sax <i>Hall Lte</i> additives <i>no add.</i>					
Plug down @ <i>6:00 AM</i> (AM) (PM) Date <i>12/11/79</i>					
Cement circulated <i>yes</i> No. of Sacks <i>225</i>					
Cemented by <i>Halliburton</i> Witnessed by <i>Mike Stubbfield</i>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

H. Stubbfield 1008