

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collins + Collins</u>		Lease <u>Wolf</u>		Well # <u>3</u>	
Location of Well	Unit <u>M</u> <u>3305</u> <u>9700</u>	Section <u>23</u>	Township <u>17</u>	Range <u>28</u>	County <u>El Dorado</u>
Drilling Contractor <u>Yucca Drilling Co.</u>			Type of Equipment <u>Rotary to start 11-30-79</u>		
* witness <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>10 3/4"</u>	<u>8 5/8"</u>	<u>20</u>		<u>117'</u>	<u>ready-mixed</u>
<u>6 3/8"</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>800</u>	<u>250 air</u>
Casing Data:					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
<u> </u> (Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u>7 7/8"</u> Size of Casing <u>4 1/2"</u> Sacks cement required <u> </u>					
Type of Shoe used <u>6 1/2" X</u> Float collar used <u> </u> Btm 3 jts welded <u>No</u>					
TD of hole <u>810'</u> Set <u>308'</u> Feet of <u>4 1/2"</u> Inch <u>23</u> # Grade <u>J-55</u>					
New-used csg. @ <u>208'</u> with <u>250</u> sacks neat cement around shoe					
+ <u> </u> sax <u> </u> additives <u> </u>					
Plug down @ <u>7:20</u> (AM) (PM) Date <u>12/21/79</u>					
Cement circulated <u>No</u> No. of Sacks <u> </u>					
Cemented by <u>Denton Cementing</u> Witnessed by <u>Mike Stubbfield</u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u> </u>					
<u>No centralizers</u>					

12/26/77

'Plan 1' To 200' pumped 5000 cu. ft. 2 to be
trapped filler hole.

2. 1st to 142 pumped 50 ex
Tagged To C.

3 Run 1" to 130' pumped 65x cont circulated.
Tagged Toc.