

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Callan Energy Inc.</i>		Lease <i>State B 1111 2.1</i>		Well # <i>11</i>	
Location of Well	Unit <i>1650N 330E</i>	Section <i>22</i>	Township <i>17</i>	Range <i>28</i>	County <i>El Paso</i>
Drilling Contractor	<i>Guerra Drilling Co.</i>		Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>9.5</i>		<i>800</i>	<i>250 line</i>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole *7 7/8* Size of Casing *4 1/2* Sacks cement required *100 SX50-50 Pos*

Type of Shoe used *Guide* Float collar used *Insert Float* Btm 3 jts welded *Yes*

TD of hole *832* Set *834* Feet of *4 1/2* Inch *9.5* # Grade *J-55*

New-used csg. @ *832* with *100* sacks neat cement around shoe  
+ *sax 50-50 Pos* additives *+ 175 SX Hewco Lite*

Plug down @ *10:00* (AM) (PM) Date *3-22-80 1/4 Flo-Seal*

Cement circulated *Yes* No. of Sacks *20*

Cemented by *Hewco* Witnessed by *B.W. Weaver*

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_