

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Collier Energy Inc.</i>		Lease <i>State B 1969 In 2</i>		Well # <i>14</i>	
Location of Well	Unit <i>16503 1650e</i>	Section <i>22</i>	Township <i>17</i>	Range <i>28</i>	County <i>CRDy</i>
Drilling Contractor <i>Gusca Drilling Co.</i>			Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <i>7 7/8</i>	<i>4 1/2</i>	<i>9.5</i>		<i>800</i>	<i>250 cins</i>

Casing Data:

Surface _____ joints of *4 1/2* inch *9.5* # Grade *J-55*

Yes (Approved) (Rejected)

Inspected by *B.W. Weaver* date *3-1-80*

Cementing Program

Size of hole *7 7/8* Size of Casing *4 1/2* Sacks cement required *100*

Type of Shoe used *Guide* Float collar used *Insert* Btm 3 jts welded *yes*

ID of hole *810* Set *810* Feet of *4 1/2* inch *9.5* # Grade *J-55*

New-used csg. @ *810* with *100* sacks neat cement around shoe

+ *150* sax *Hewco Lite* additives *#6 salt #5 gelsolite #14 LB FloSeal*

Plug down @ *11:00* (AM) (PM) Date *3-1-80*

Cement circulated *yes* No. of Sacks *20 SX*

Cemented by *Hewco* Witnessed by *B.W. Weaver*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____