

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Collier Energy Inc.</i>		Lease <i>State B 1969 Jr. 2</i>		Well # <i>15</i>	
Location of Well	Unit <i>16503 2310e</i>	Section <i>22</i>	Township <i>17</i>	Range <i>28</i>	County <i>Eddy</i>
Drilling Contractor <i>Yucra Drilling Co.</i>			Type of Equipment <i>Rotary</i>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <i>7 7/8"</i>	<i>4 1/2"</i>	<i>9.5</i>		<i>800</i>	<i>250 C/s</i>

Casing Data:

Surface *22* joints of *4 1/2* inch *9.5* # Grade *J-55*
☒ (Approved) ☐ (Rejected)

Inspected by *mw* date *2/24/80*

Cementing Program

Size of hole *7 7/8* Size of Casing *4 1/2* Sacks cement required *275 SX*

Type of Shoe used *Float* Float collar used *—* Btm 3 jts welded *Yes*

TD of hole *800* Set *810* Feet of *4 1/2* Inch *9.5* # Grade *J-55*

New-used csg. @ *800* with *100* sacks neat cement around shoe

+ *175* sax *Halliburton* additives *8" 5/16" P. Sh. 3 LFR 2*

Plug down @ *4:10* (AM) (PM) Date *2/24/80*

Cement circulated *Yes* No. of Sacks *20*

Cemented by *H. H. Burton* Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *2 Centralizers on 1st 2 btm 2 Jts*