

## OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501Form C-103  
Revised 10-1

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	

SEP 4 1981

O. C. D.

## SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE.

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL ☒ GAS ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER A 330 FEET FROM THE North LINE AND 330 FEET FROM  
THE East LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3470' GR

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil &amp; Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

Johnson FE

9. Well No.

3

10. Field and Pool, or Wildcat

Eagle Creek SA

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
FULL OR ALTER CASING ☐PLUG AND ABANDON ☐  
CHANGE PLANS ☐OTHER ☐REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒OTHER ☐ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole 8:00 AM 8-26-81. Ran 7 jts of 10-3/4" 32# K-55 casing set at 295'. 1-Texas Pattern notched guide shoe set at 295'. Flapper float set at 255'. Cemented w/300 sacks Class C 3% CaCl<sub>2</sub>. Compressive strength of cement - 1875 in 12 hrs. PD 5:15 PM 8-26-81. Bumped plug to 1000 psi, released pressure & float held okay. Circulated 35 sacks to pit. WOC 12 hrs. Reduced hole to 9-1/2". Drilled plug and resumed drilling. TD 1220'. Ran 28 jts of 7" 20# K-55 T&C casing set at 1220'. 1-Notched guide shoe set at 1220'. Flapper insert float set at 1175'. Cemented w/150 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 2% CaCl, 10#/sack Gilsonite, 400 sacks 50/50 Poz, 2# sack Permacheck, 1/2#/sack Celloseal, 3% CaCl. Tailed w/150 sacks Class C 2% CaCl. PD 2:30 PM 8-28-81. Cement did not circulate. Bumped plug to 750 psi, released pressure & float held okay. WOC 6 hrs. Ran Temperature survey & found top of cement at 720'. Ran 1". Tagged cement at 580'. Spotted 50 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 11:30 PM 8-28-81. WOC 1 hr. Ran 1". Tagged cement at 478'. Spotted 50 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 1:00 AM 8-29-81. WOC 1 hr. Ran 1". Tagged cement at 416'. Spotted 50 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 2:30 AM 8-29-81. WOC 2 hrs. Ran 1". Tagged cement 352'. Spotted 50 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 4:45 AM 8-29-81. WOC 1 hr. Ran 1". Tagged cement at 352'. Spotted 25 sacks Class C 3% CaCl. PD 6:30 AM 8-29-81. WOC 2 hrs. (cont'd)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jeanine GoodallTITLE Engineering SecretaryDATE 9-1-81APPROVED BY Mike WilliamsTITLE OIL AND GAS INSPECTORDATE SEP 9 1981

CONDITIONS OF APPROVAL, IF ANY:

Page 2 -

Johnson FE #3  
330' FNL & 330' FEL, Sec. 23-T17S-R25E  
Eddy County, New Mexico

Ran 1". Tagged cement at 352'. Spotted 25 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 9:08 AM 8-29-81. WOC 1 hr.  
Ran 1". Tagged cement at 320'. Spotted 25 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 10:15 AM 8-29-81. WOC 1-1/2 hrs.  
Ran 1". Tagged cement at 320'. Spotted 25 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 12:00 noon 8-29-81. WOC 1 hr.  
Ran 1". Tagged cement at 300'. Spotted 25 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 1:15 PM 8-29-81. WOC 1 hr.  
Ran 1". Tagged cement at 280'. Spotted 50 sacks Thixolite, 2#/sack Permacheck, 1/2#/sack Celloseal, 10#/sack Gilsonite, 3% CaCl. PD 2:15 PM 8-29-81. Circulated 10 sacks to pit. WOC 31 hrs & 45 minutes. Nippled up & tested to 1000 psi, okay. Reduced hole to 6-1/2". Drilled plug & resumed drilling.