

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 120
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Bowman N.A.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980S+W</i>	Section <i>4</i>	Township <i>17</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Landis Rig &</i>		Type of Equipment <i>Rotary</i>			

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 7/8</i>	<i>48</i>		<i>400</i>	<i>390 lbs.</i>
* <i>12 1/4</i>	<i>8 5/8</i>	<i>24</i>		<i>1350</i>	<i>650 "</i>
<i>7 7/8</i>	<i>5 1/2 or 4 1/2</i>			<i>8230</i>	

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole *12 1/4"* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

ID of hole *1360'* Set *1360'* Feet of *8 5/8* Inch *24* # Grade *J-55*

(New)-used csg. @ *1360'* with *5027 cc* sacks neat cement around shoe

+ *500* sax *6 5/35* per. additives *1/4# coloff, 8# Koloite, 490 gal, 392 cc*

Plug down @ *3345* (AM) (PM) Date *3/30/80*

Cement circulated *No* No. of Sacks *-0-*

Cemented by *Dowell* Witnessed by *Michael Stullerfield*

Temp. Survey ran @ *10:00 (AM)* (PM) Date *3/31/80* top cement @ *515'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks:

Full returns drilled with Fresh water.

No centralizers

last daily track @ 1205'

1. Run 1" Tagged TOC @ 525'
Pumped 50 sx class C 490cc
2. Run 1" Tagged TOC @ 525'
Pumped 50 sx class C 490cc
3. Run 1" Tagged TOC @ 420'
Pumped 164 sx class C 490cc
cement circulated.