

DISTRIBUTION		
BY A FE	I	
LE	I	✓
U.S.		
ND OFFICE		
ERATOR	I	

NEW MEXICO OIL CONSERVATION COMMISSION

C-102 and C-103
Effective 1-1-65

RECEIVED

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Bowman NA Com
9. Well No. 1 1
10. Field and Pool, or Wildcat Und. POW Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS APR 28 1980
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER-
Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th Street - Artesia, NM 88210
Location of Well
UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM
West 4 17S 26E
15. Elevation (Show whether DF, RT, GR, etc.)
3358

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PLUG OR ALTER CASING ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☒ CASING TEST AND CEMENT JOB ☒ OTHER ☐
PLUG AND ABANDON ☐ CHANGE PLANS ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 9:00 AM 3-29-80. Drilled to 415' and ran 12 joints of 13-3/8" 54.50# ST&C (420') of casing set at 415'. 1-Texas Pattern guide shoe at 415' and insert float at 375'. Cemented w/400 sacks of Class C 4% CaCl. Slurry weight 14.8, 1.32 cu.ft/sack. Compressive Strength at 70 degrees 1023 psi in 12 hours. PD 6:15 PM 3-29-80. Cement circulated 40 sacks to surface. WOC 12 hours, backed off and reduced hole to 12¼", drilled plug & tested to 600# OK and resumed drilling.

TD 1363' - Ran 34 jts of 8-5/8" 24# J-55 ST&C (1365') of casing set at 1363'. 1-Regular Pattern guide shoe at 1363'. Insert float at 1323'. Cemented w/500 sacks 65-35 Poz, 8#/sack Kolite, 1/4#/sack cellpflakes, 4% gel, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 3:45 AM 3-31-80. Cement did not circulate. WOC 6 hours, ran Temperature Survey and found top of cement at 525'. Ran 1" & tagged cement at 525', spotted 50 sacks Class C 4% CaCl. PD 11:00 AM 3-31-80. WOC 2 hrs, ran 1" and tagged cement at 525', sptd 100 sacks Class C 4% CaCl. WOC. Ran 1" and tagged cement at 420', sptd 164 sacks Class C 4% CaCl. PD 2:30 PM 3-31-80. Cmt 10 sx to surface. WOC 18 hrs, NU & tested to 1000# OK, reduced hole to 7-7/8", drld plug & tstd 600# OK and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Christine Tomlinson TITLE Geol. Secty. DATE 4-26-80

APPROVED BY For Record Only TITLE SUPERVISOR, DISTRICT II DATE APR 30 1980

CONDITIONS OF APPROVAL, IF ANY: