

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐	JUL 30 1980	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	O. C. D.	8. Farm or Lease Name Bowman NA Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	ARTESIA, OFFICE	9. Well No. 1
4. Location of Well UNIT LETTER K .1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 4 TOWNSHIP 17S RANGE 26E NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3358' GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	FLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOG ☐	Set Prod. csg. ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8200'; PBTD 7005' - Ran 202 joints of 4½" 10.5# K-55 ST&C (7045') of casing set at 7045'. 1-Diff-fill float collar at 7005'. 10-centralizers. Cemented w/250 gallons CW 100, 665 sacks 50-50 Poz, 2/10% D-108, 2/10% D-65, 3#/sack KCL. Displaced first 40 bbls w/2% KCL. PD 2:00 PM 4-19-80. WOC. Tested to 1500# OK. Top of cement at 5800'.

TD 8200'; PBTD 7005' - WIH w/casing gun on wireline and perforated 6877-83' w/12 .34" holes (2spf). POOH. WIH w/2-3/8" tubing and Guiberson packer, set packer at 6838' and treated perforations w/2000 gallons 15% DS-30 acid w/nitrogen. Recovered 64 bbls treating fluid w/nitrogen. Swabbed. Swabbed a total of 62 bbls into tank (52 BW and 11 BO). Swabbed well dry. Treated perforations w/8000 gallons acid, 500 gallons 15% DS-30 and 7500gallons 15% Series 72 and CO2. Swabbed well recovered 29 BW and 6 BO. Pulled packer out of hole and installed pumping equipment. Recovered load. Well pumping 7 BOPD. and 1 BWPD.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine J. Anderson TITLE Geol. Secty. DATE 7-29-80

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE JUL 31 1980

CONDITIONS OF APPROVAL, IF ANY: