

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-78

RECEIVED

APR 15 1983

5a. Indicate Type of Lease

State ☐

Fee ☒

3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. D.

ARTESIA, OFFICE

OIL WELL ☒

GAS WELL ☐

OTHER ☐

1. Name of Operator

Yates Petroleum Corporation ☒

8. Farm or Lease Name

Gissler AV

2. Address of Operator

207 South 4th St., Artesia, NM 88210

9. Well No.

17

3. Location of Well

UNIT LETTER C 990 FEET FROM THE North LINE AND 1650 FEET FROM
THE West LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.

10. Field and Pool, or Wildcat

Eagle Creek SA

15. Elevation (Show whether DF, RT, GR, etc.)

3499' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Intermediate Casing ☒

OTHER ☐

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 30 joints of 7" 23# J-55 ST&C casing set 1150'. 1-Texas Pattern notched guide shoe set 1150'. Insert float set 1110'. Cemented w/375 sacks Pacesetter Lite, 1/4# celloseal, 10# gilsonite, 3% CaCl2. Tailed in w/175 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 6:30 PM 3-17-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 40 sacks. WOC 20 1/2 hrs. Drilled out 3:00 PM 3-18-83. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 6-1/4". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 4-13-83

APPROVED BY _____

TITLE Original Signed By

Leslie A. Clements

DATE APR 20 1983

CONDITIONS OF APPROVAL, IF ANY:

Supervisor District II