

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Collier Energy Inc.</i>		Lease <i>State B 1969 L. 3</i>		Well # 20 <i>21</i>	
Location of Well	Unit <i>R</i> <i>231054e</i>	Section <i>22</i>	Township <i>17</i>	Range <i>28</i>	County <i>El Paso</i>
Drilling Contractor	<i>yucca d co</i>		Type of Equipment <i>Rotary</i>		

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <i>6 7/8"</i>	<i>4 1/2"</i>	<i>9.5</i>		<i>860</i>	<i>250 cwt</i>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole *7 7/8* Size of Casing *4 1/2* Sacks cement required *250 sxc*

Type of Shoe used *6 5/8 Bit* Float collar used *Insert* Btm 3 jts welded *yes*

TD of hole *800* Set *798* Feet of *4 1/2* Inch *9.5* # Grade *J-55*

New-used csg. @ *798* with *250* sacks neat cement around shoe
+ _____ sax _____ additives

Plug down @ _____ (AM) (PM) Date *5-21-80*

Cement circulated _____ NO _____ No. of Sacks _____

Cemented by *Denton* Witnessed by *R. W. Weaver*

Temp. Survey ran @ *11:00* (AM) (PM) Date *5/21/80* top cement @ *90'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: *Cmt. to surface, Toc by survey 90' - req. 150 sxs to fill to surface by cementing Down between 4 1/2" csg. & 7 7/8" hole.*