

N.I. I.C.D. COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to back to a well or to a reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
William N. Beach

3. ADDRESS OF OPERATOR  
P. O. Box 3669, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL, 330' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒ Drilling Activity  
☒ Setting Surface casing.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. L. Cherryhomes TITLE CLERK DATE 6-13-81

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN  
APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

JUL 9 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions on Reverse Side

Section 26, T-16-S, R-28-E,  
660' FSL & 330' FEL,  
Eddy County, NM  
GL elevation: 3583.7

Drilling Contractor: S & D Equipment  
Smokey Adamson

- 4-16-81 Moving in and rigging up cable tool.
- 4-17-81 Spudded Well.
- 4-18-81 Drilling at 51' in surface rock.
- 4-19-81 Did not work--Easter.
- 4-24-81 Drilling at 116' in redbeds.
- 4-27-81 Drilling at 200', redbeds.
- 4-28-81 Drilling at 215' in redbeds. Hole caving.
- 5-1-81 Set 215' surface casing.
- 5-4-81 Drilling at 293', anhydrites and salt stringers. Preparing to run 8-5/8" casing.  
TD 297' in anhydrites and salt stringers. Set 293' 8-5/8" 20# casing. Cemented with 250 sx. Cement did not circulate. Got permission from Oil Conservation Commission to put redi-mix from surface. Plugged down 12:00 midnight 5-4-81.
- 5-5-81 W.O.C.
- 5-7-81 Bail hole dry. Left overnight. Hole still dry next morning.
- 5-9-81 Resumed drilling.
- 5-11-81 375' in salt and anhydrite.
- 5-15-81 500', anhydrites and lime stringers.
- 5-16-81 580', anhydrites, lime, and shale stringers.
- 5-17-81 Did not work.
- 5-19-81 610', anhydrites and shale stringers.
- 5-21-81 655' in anhydrites.
- 5-22-81 680' in anhydrites.
- 5-26-81 735', anhydrite, working on rig.
- 5-28-81 750', drilling.
- 6-1-81 820', drilling in anhydrite and red beds.
- 6-2-81 840', drilling.
- 6-3-81 849', drilling.
- 6-4-81 drilling at 875'. Cut 20' in sand and dolomite. No show.
- 6-8-81 890' drilling.