

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 5760
7. Unit Agreement Name
8. Farm or Lease Name State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Colorado Interstate Gas Company ✓
3. Address of Operator 415 West 8th, Amarillo, Texas 79101
4. Location of Well UNIT LETTER <u>F</u> <u>1000</u> FEET FROM THE <u>North</u> LINE AND <u>2010</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>16S</u> RANGE <u>28E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3553' G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Plugging lower section of borehole</u> <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Colorado Interstate Gas Company reached total depth of 9738' on June 10, 1980. On June 13, 1980, plugs were spotted in the lower portion of the wellbore as per directions from the New Mexico Oil Conservation Commission. Thirty-five sacks neat cement plugs were spotted as follows: 9400', 7650', 6825', 5425', and 3800'.

After the plugs were spotted, 5 1/2" casing was run and set @ 3603' G.L. The casing consisted of 1574' of 15.5 lb./ft. and 2029' of 14 lb./ft. The casing was cemented with 170 sacks of Class 'H' with additives. Plug was bumped at 8:00 p.m. on June 13, 1980.

RECEIVED

JUN 19 1980

O. C. D.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>June 18, 1980</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>JUN 20 1980</u>

CONDITIONS OF APPROVAL, IF ANY: