

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collier & Collier</u>		Lease <u>Wolf</u>		Well # <u>4</u>	
Location of Well	Unit <u>m</u>	Section <u>23</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor	<u>Yucca Drilg Co</u>		Type of Equipment <u>Rotary</u>		
* witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>10 3/4</u>	<u>8 5/8</u>	<u>20#</u>		<u>100'</u>	<u>Circ</u>
<u>6 5/8</u>	<u>4 1/2</u>	<u>9.5#</u>		<u>800'</u>	<u>Circ</u>
Casing Data:					
Surface <u> </u> joints of <u>4 1/2</u> inch <u>9.5</u> # Grade <u>J-55</u>					
<u>(Approved)</u> (Rejected)					
Inspected by <u>Larry Brooks</u> date <u>5/23/80</u>					
Cementing Program					
Size of hole <u>6 5/8"</u> Size of Casing <u>4 1/2"</u> Sacks cement required <u>250</u>					
Type of Shoe used <u>TYPE M NOTCHED</u> Float collar used <u>yes</u> Btm 3 jts welded <u>No</u>					
TD of hole <u>850'</u> Set <u>850</u> Feet of <u>4 1/2"</u> Inch <u>9.5</u> # Grade <u>J-55</u>					
<u>New</u> -used csg. @ <u>848</u> with <u> </u> sacks neat cement around shoe					
+ <u>250</u> sax <u>50/50 POZ. (cl.c)</u> additives <u>2% gpl, 3% CFR₂</u> 6lbs salt/sk. wgt. 14.2					
Plug down @ <u>7:15</u> (AM) <u>(PM)</u> Date <u>5/23/80</u>					
Cement circulated <u>NO</u> No. of Sacks <u> </u>					
Cemented by <u>HALLIBURTON</u> Witnessed by <u>Larry Brooks</u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>NO BASKET.</u>					