

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

ARTESIA, NM 88210  
RECEIVED

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 9987

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Exxon Federal

9. WELL NO.

#2  
Wildcat

11. SEC. T. R. M., OR BLK. AND  
SURVEY OR AREA

Sec 30 T16S R29E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different level or.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER

Plug & Abandon DEC 2 1982

2. NAME OF OPERATOR

MoroilCo, Inc.

O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE  
P.O. Drawer I, Artesia, N.M. 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980 from South line 1980 from East line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3664.3' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 3520' Plug & Abandon 12-28-82

Bridge plug set @ 2450' with 35' of cement

Bridge plug set @ 2350' with 35' of cement

Set 25sx. cement plug @ 1890-1790

Set 25 sx.cement plug @ 1150-1050

Set 25 sx.cement plug @ 340-240 (inside & outside of 4 1/2" csg.)

Set 15 sx.cement plug @ 30' to surface.

plug mud of 25sx. 100 bbl. of water

Pits have been closed, pad & road have rinned and

location has been cleaned off.

RECEIVED  
FEB 10 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State use only)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FOR

JAMES A. GILLHAM \*See Instructions on Reverse Side  
DISTRICT SUPERVISOR

20-44-23333

6-11-80  
Duel Zetudog  
520' - 2000'  
Comp. Neut.  
2000' - 2320'