

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Vates Petroleum Corp</u>			Lease <u>Manatee NT Com</u>		Well # <u>1</u>
Location of Well	Unit <u>H</u>	Section <u>30</u>	Township <u>17</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Capitan</u>			Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48# H-40		360'	Circ
* 12 1/4	8 5/8	24# K-SS		1300	Circ
7 7/8	4 1/2 - 5 1/2	10.50 17# K-SS		850' TD	

Casing Data:

Surface 29 joints of 8 5/8 inch 24 # Grade K-SS

(Approved) (Rejected)

Inspected by Mike Stubblefield date 3/16/81

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1300' Set 1300' Feet of 8 5/8" Inch 24 # Grade K-SS

(New) used csg. @ 1300' with 50 2% sacks neat cement around shoe
+ 300 sax 5/35 poz. additives (470 gal., 8# K-SS, 1/4# celo, 390cc)

Plug down @ 8:00 (AM) (PM) Date 3/18/81

Cement circulated No No. of Sacks -0-

Cemented by Dowell Witnessed by Mike Stubblefield

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 400.5x C 390cc

Post circ. @ 800'

Post daily check @ 810'