

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

JUN 18 1980

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | 1 |
| FILE | 1 |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | 1 |

| |
|--|
| 5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> |
| 5. State Oil & Gas Lease No. |
| 7. Unit Agreement Name |
| 8. Farm or Lease Name Coll "LD" Com |
| 9. Well No. 1 |
| 10. Field and Pool, or Wildcat Und. Kennedy Farms Morrow |
| 12. County Eddy |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☒ WELL OTHER-
2. Name of Operator
Yates Petroleum Corporation
3. Address of Operator
207 South Fourth Street - Artesia, NM 88210
4. Location of Well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 17S RANGE 26E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3351' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
|--|---|---|--|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> | OTHER Set and cement 8-5/8" casing <input checked="" type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work); SEE RULE 1103.

Spudded a 17-1/2" hole at 8:30 AM 6-14-80.

TD 400'. Ran 11 joints of 13-3/8" 48# H-40 (406') of casing set at 400'. 1-Texas Pattern guide shoe at 400'. Insert float at 360'. Cemented w/400 sacks Class "C" 4% CaCl. Slurry weight 14.8, 1.32 cu.ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. PD 6:00 PM 6-14-80. Circulated 65 sacks. WOC 12 hours. Backed off and reduced hole to 12-1/4". Drilled plug and tested to 600#, OK. Resumed drilling.

TD 1401'. Ran 35 joints of 8-5/8" 24# J-55 ST&C (1405') of casing set at 1401'. 1-guide shoe at 1401'. Insert float at 1361'. Used 1 centralizer. Cemented w/650 sacks Howco Lite, 10#/sack gilsonite, 1/4# flocele and 2% CaCl. Tailed in w/150 sacks Class "C" + 2% CaCl. PD 3:00 AM 6-16-80. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 680'. Ran 1" and tagged cement at 580'. Spotted 145 sacks Class "C" + 4% CaCl. PD 11:30 AM 6-16-80. Circulated 10 sacks to pit. Cement fell back. Filled hole w/3 yards of Ready-Mix. WOC 18 hours. Nippled up and tested to 1500#, OK. Reduced hole to 7-7/8". Drilled plug and tested to 600#, OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine L. Anderson TITLE Geological Secretary DATE June 18, 1980

APPROVED BY W. A. Gracett TITLE SUPERVISOR, DISTRICT II DATE JUN 18 1980

CONDITIONS OF APPROVAL, IF ANY: