

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Jackson Estate BY</u>		Well # <u>10</u>	
Location of Well	Unit <u>2310P</u> <u>1650W</u> F	Section <u>22</u>	Township <u>17</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor <u>L & M Drilling Co</u>			Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32#		320'	350 SX Circ
9 1/2"	7"	20#		1150'	850 SX Circ
6 1/4"	4 1/2 or 5 1/2	10.5# + 15.5#		1500±	Circ

Casing Data:

Surface _____ joints of 7" inch 20 # Grade J-SS
(Approved) (Rejected)

Inspected by M.S. date 8/9/80

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1152' Set 1152' Feet of 7" Inch 20 # Grade J-SS

New-used csg. @ 1152' with 150sx sacks neat cement around shoe
+ 200 sax C additives 390cc

Plug down @ 1830 (AM) (PM) Date 8/9/80

Cement circulated yes No. of Sacks 50sx

Cemented by Dowell Witnessed by Mike Stillfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: + 400 SX 6 5/35 poz. (490gel, 8# Kofite, 1/4# celoflubes, 390cc)

100 cement bags

last day break @ 1040'