

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Jackson Estate BY	
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		9. Well No. 11	
4. Location of Well UNIT LETTER <u>F</u> . <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>22</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> N.M.P.M.		10. Field and Pool, or Wildcat Eagle Creek S.A.	
15. Elevation (Show whether DF, RT, GR, etc.) 3534' GR		12. County Eddy	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 10:15 PM 7-31-80.  
TD 363' - Ran 9 joints of 10-3/4" 40.50# K-55 ST&C (365') of casing set at 363'. 1-Flapper float at 320'. Cemented w/200 sacks of Class C 4% CaCl.  
PD 1:00 PM 8-1-80. Circulated 10 sacks of cement to the surface. WOC 12 hours, backed off, reduced hole to 9 1/2", drilled plug, tested to 600# OK and resumed drilling.  
TD 1167' - Ran 28 joints of 7" 20# K-55 ST&C (1167') of casing set at 1167'. 1-Guide shoe at 1167' & Flapper float at 1127'. Cemented w/200 sacks of Class C Neat, 500 sacks 65-35 Poz, 8# D-42, 1/4# D-29, 3% CaCl, 1/4% D-20. Tailed in w/150 sacks of Class C 2% CaCl. PD 5:15 PM 8-3-80. Circulated 20 sacks of cement to the surface. WOC 18 hours, NU, tested to 1500# OK, reduced hole to 6 1/4", drilled plug, tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 8-7-80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 11 1980

CONDITIONS OF APPROVAL, IF ANY: