

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

1650/S
430/11

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Jackson Estate BY</u>		Well # <u>12</u>	
Location of Well	Unit <u>2310N 330W E</u>	Section <u>22</u>	Township <u>17</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor	<u>L + M Drilling Co</u>		Type of Equipment <u>Rotary</u>		
* Witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 3/4"</u>	<u>32 #</u>		<u>320</u>	<u>350 SX Circ</u>
* <u>9 1/2"</u>	<u>7"</u>	<u>20 #</u>		<u>1150</u>	<u>850 SX Circ</u>
<u>6 1/4"</u>	<u>4 1/2 + 5 1/2</u>	<u>10.5 # + 15.5 #</u>		<u>1500 ±</u>	<u>Circ</u>
Casing Data:					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
(Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u>9 7/8"</u> Size of Casing <u>7"</u> Sacks cement required <u> </u>					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1134'</u> Set <u>1134'</u> Feet of <u>7"</u> Inch <u>20</u> # Grade <u>K-SS</u>					
New-used csg. @ <u>1134'</u> with <u>100 370cc</u> sacks neat cement around shoe					
+ <u>4100</u> sax <u>15/35 popo</u> additives <u>2# permachek, 1/2# calmed, 370cc</u>					
Plug down @ <u>8:00</u> (AM) (PM) <u>PM</u> Date <u>9/13/81</u>					
Cement circulated <u>No</u> No. of Sacks <u>-0-</u>					
Cemented by <u>Western Co</u> Witnessed by <u>Mike Stubblefield</u>					
Temp. Survey ran @ <u>2:00</u> (AM) (PM) <u>AM</u> Date <u>9/14/81</u> top cement @ <u>100'</u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>+50sx Thixolite (2# permachek, 1/2# calmed, 10# gils, 270cc)</u>					
No centralizer					
most circ. 2950+ required					
most dily break @ 1038'					

1. Ran 1" + tagged to c @ 115'
Pumped 72 sx @ 370cc.
cement circulated to surface.