

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <b>Yates Petr Corp</b>			Lease <b>Jackson Estate BY</b>		Well # <b>13</b>
Location of Well	Unit <b>2310S 990W L</b>	Section <b>22</b>	Township <b>17</b>	Range <b>25</b>	County <b>Edy</b>
Drilling Contractor	<b>L+M Drllg Co</b>		Type of Equipment <b>Rotary</b>		

\* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32#		320	Circ 350 Sx
9 1/2"	7"	20#		1150	Circ 850 Sx
6 1/4"	4 1/2" + 5 1/2"	10.5#-15.5#		1500	Circ

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 9 7/8" Size of Casing 7" Sacks cement required 550

Type of Shoe used Notched Float collar used inst. float Btm 3 jts welded yes

TD of hole 1143 Set 1143 Feet of 7 Inch 17 # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with 150 sacks neat cement around shoe C.I.C 3% CaCl<sub>2</sub>  
+ 400 sax 65/35 po<sub>2</sub> additives \_\_\_\_\_

Plug down @ 12:45 (AM) (PM) Date 9/19/81

Cement circulated 400 No. of Sacks 45 Sxs.

Cemented by WESTERN Witnessed by LARRY BROOKS

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_