

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Gissler AV</u>		Well # <u>20</u>	
Location of Well	Unit <u>F</u>	Section <u>23</u>	Township <u>11</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor	<u>L & M Drilling Co</u>		Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32 #		320'	350 SX - Circ
* 9 1/2"	7"	20 #		1150'	850 SX - Circ
6 1/4"	4 1/2" or 5 1/2"	10.5 # & 15.5 #		1500'	Circ

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required _____

Type of Shoe used guide Float collar used inert Btm 3 jts welded yes

TD of hole 1176' Set 1176' Feet of 7" Inch 20 # Grade J-55

New-used csg. @ 1176' with 1502' sacks neat cement around shoe

+ 200 sax C additives 3% occ

Plug down @ 8:00 (AM) (PM) Date 7/28/80

Cement circulated yes No. of Sacks 155x

Cemented by Dowell Witnessed by Mike Shultzfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: + 700 (4% gel, 8# Kofite, 1/4# colo, 3% occ)

Darken @ 700' - 515'

lost circ. @ 744'

lost plug back @ 1071'