

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collier Energy Inc</u>		Lease <u>State B IIII Tr 2</u>		Well # <u>16</u>	
Location of Well	Unit <u>2310N 1650W F</u>	Section <u>22</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor	<u>Yucca Drilling Co</u>		Type of Equipment <u>Rotary</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>7 7/8</u>	<u>4 1/2"</u>	<u>9.5#</u>		<u>800</u>	<u>Circ</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 7 7/8 Size of Casing 4 1/2 Sacks cement required 250

Type of Shoe used Guide Float collar used no Btm 3 jts welded yes

TD of hole 715 Set 709 Feet of 4 1/2 Inch 9.5 # Grade J-55

New-used csg. @ 709 with 250 sacks neat cement around shoe  
+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ 1:30 (AM) (~~PM~~) Date 11-1-80

Cement circulated yes No. of Sacks 10-SX

Cemented by Denton Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_