

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collier Energy Inc.</u>		Lease <u>St. B III Tr - 2</u>		Well # <u># 17</u>	
Location of Well	Unit <u>1630 N 1630 W</u> <u>F</u>	Section <u>22</u>	Township <u>17 S</u>	Range <u>28 E</u>	County <u>EDDY</u>
Drilling Contractor <u>Yucca Drilling Co</u>	Type of Equipment <u>Rotary</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>1 7/8"</u>	<u>4 1/2"</u>	<u>9 1/2 #</u>		<u>800</u>	<u>circ</u>

Casing Data:

Surface 30 joints of 4 1/2 inch 9 1/2 # Grade T-24

(Approved) (Rejected)

Inspected by Darryl Brooks date 1-23-80

Cementing Program

Size of hole 7 7/8 Size of Casing 4 1/2" Sacks cement required 250

Type of Shoe used Type M Float collar used insert Btm 3 jts welded ---

TD of hole 840 Set 840 Feet of 4 1/2 Inch 9 1/2 # Grade T-24

New used csg. @ 840 with 250 sacks neat cement around shoe Cl. C

+ --- sax --- additives

Plug down @ --- (AM) (PM) Date ---

Cement circulated Yes No. of Sacks 25 sx

Cemented by Denton Witnessed by ---

Temp. Survey ran @ --- (AM) (PM) Date --- top cement @ ---

Casing test @ --- (AM) (PM) Date ---

Method Used --- Witnessed by ---

Checked for shut off @ --- (AM) (PM) Date ---

Method used --- Witnessed by ---

Remarks: Centralizers @ - 810' & 778'

Hit H₂O @ - 115'

Ready-mixed well to surface 1 1/2 yds. M.S. 10/2/80