

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>RPM Energy Inc</u>		Lease <u>State</u>		Well # <u>1</u>	
Location of Well	Unit <u>23105 660E I</u>	Section <u>16</u>	Township <u>16</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Sinclair Operations</u>		Type of Equipment <u>Rotary</u>		
*Witness <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14"</u>	<u>12 3/4</u>	<u>33 #</u>		<u>400'</u>	<u>120 SX Circ</u>
<u>11"</u>	<u>8 5/8</u>	<u>24 #</u>		<u>1100'</u>	<u>350 SX Circ</u>
<u>7 7/8"</u>	<u>4 1/2</u>	<u>9.5 #</u>		<u>1700'</u> <u>TD</u>	<u>275 SX</u>
Casing Data:					
Surface <u>25</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>J-55</u>					
<u>Approved</u> (Rejected)					
Inspected by <u>Mike Stubblefield</u> date <u>10-3-80</u>					
Cementing Program					
Size of hole <u>11</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>800 SX</u>					
Type of Shoe used <u>Guide Float collar</u> used <u>Inst.</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1060</u> Set <u>1060</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
<u>New</u> -used csg. @ <u>1060</u> with <u>800</u> sacks neat cement around shoe C.I. H. + <u>      </u> sax <u>      </u> additives					
Plug down @ <u>6:15</u> (AM) <u>(PM)</u> Date <u>10-4-80</u>					
Cement circulated <u>yes</u> No. of Sacks <u>150</u>					
Cemented by <u>Morphree Serv. Inc.</u> Witnessed by <u>Larry Brooks</u>					
Temp. Survey ran @ <u>      </u> (AM) (PM) Date <u>      </u> top cement @ <u>      </u>					
Casing test @ <u>      </u> (AM) (PM) Date <u>      </u>					
Method Used <u>      </u> Witnessed by <u>      </u>					
Checked for shut off @ <u>      </u> (AM) (PM) Date <u>      </u>					
Method used <u>      </u> Witnessed by <u>      </u>					
Remarks: <u>Centralizers - 1046', 928', 840'</u>					
<u>Last. dring, bk - 1018</u>					