

DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old  
C-102 and C-103  
Effective 1-1-64

NOV 14 1980

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	B-1969

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT -" (FORM C-101) for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Collier Energy, Inc.	8. Farm or Lease Name State B-1969, Tr. 4
3. Address of Operator P. O. Box 798, Artesia, New Mexico 88210	9. Well No. #24
4. Location of Well UNIT LETTER D 990 FEET FROM THE N LINE AND 330 FEET FROM THE W LINE, SECTION 22 TOWNSHIP 17-S RANGE 28-E NMPM.	10. Field and Pool, or Wildcat Und. East Empire Yates 7-R
15. Elevation (Show whether DF, RT, GR, etc.) 3558-GL	12. County Eddy

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

## SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

November 1, 1980: Spudded well.

November 2, 1980: Ran 140' of 8" PVC. Cemented with 60 SXS Class C with 4% CaCl. WOC 12 hrs. Compressive strength of Class C with 4% CaCl after 8 hrs. @ 65° at 605#.

November 3, 1980: T.D. at 715'. Ran 710' of 4 1/2", 9.5# casing with float shoe. Set shoe at 710'. Cemented casing with 250 SXS of Class C neat cement. Cement circulated 20 SXS to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald Craig TITLE President DATE 11-12-80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 19 1980

CONDITIONS OF APPROVAL, IF ANY: