

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 10  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <b>Collier Energy Inc</b>		Lease <b>State B 1969 Tr 4</b>		Well # <b>26</b>	
Location of Well	Unit <b>330N 950W D</b>	Section <b>22</b>	Township <b>17</b>	Range <b>28</b>	County <b>Eddy</b>
Drilling Contractor	<b>Yucca</b>		Type of Equipment <b>Rotary</b>		

**\* Witness** APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<b>7 7/8</b>	<b>4 1/2</b>	<b>9.5#</b>	<b>-</b>	<b>800'</b>	<b>250 <del>sr</del> C</b>
	<b>7"</b>			<b>184'</b>	<b>150 sr C</b>
					<b>ready mixed to surface.</b>

**\* Casing Data:**

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

**Cementing Program**

Size of hole **6 1/4"** Size of Casing **4** Sacks cement required \_\_\_\_\_

Type of Shoe used **guide** Float collar used **insert** Btm 3 jts welded **No**

TD of hole **840'** Set **835'** Feet of **4 1/2"** Inch **9.5#** Grade **J-SS**

**New**-used csg. @ **835'** with **250** sacks neat cement around shoe

+ \_\_\_\_\_ sac \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ **10:45** **(AM)** (PM) Date **10/9/80**

Cement circulated **Yes** No. of Sacks **12**

Cemented by **Denton cementing** Witnessed by **Mike Stubblefield**

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

\_\_\_\_\_

**No centralizers** **Salt water 265'**