

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

C-102 and C-103
Effective 1-1-65

NOV 17 1980

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-1969

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Plug and Abandon
2. Name of Operator Collier Energy, Inc. ✓
3. Address of Operator P.O. Box 798, Artesia, New Mexico 88210
4. Location of Well UNIT LETTER D 330 FEET FROM THE North LINE AND 330 FEET FROM West 22 TOWNSHIP 17 S RANGE 28 E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3549' GL

7. Unit Agreement Name
8. Farm or Lease Name St. B-1969, Tr. 4
9. Well No. #27
10. Field and Pool, or Wildcat East Empire Yates 7-R
12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

October 3, 1980 - Spudded well. Ran 120' of 8" PVC casing. Used 25 Sxs. mudjell and 5 Sxs. paper sill. Cemented with 60 Sxs. Class C 4% CaCl.

October 21, 1980 - Plugging Report:
Drilled to 660'. Twisted off at 460'. Washed down beside drill pipe to 480'. Ran 80 Sxs. Class C 4% CaCl cement. Pulled 200' casing. Ran 90 Sxs. Class C cement. Pulled rest of pipe.

Hole 7 7/8". 170 Sxs. Class C cement to 480'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald Craig TITLE President DATE 11/12/80

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: