

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Revised by  
C-102 and C-103  
Effective 1-1-80

NOV 17 1980

ART. 31 OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-1969

# SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER - Plug and Abandon	7. Unit Agreement Name
2. Name of Operator Collier Energy, Inc. ✓	8. Farm or Lease Name St. B-1969, Tr. 4
3. Address of Operator P.O. Box 798, Artesia, New Mexico 88210	9. Well No. #27
4. Location of Well UNIT LETTER D 330 FEET FROM THE North LINE AND 330 FEET FROM West LINE, SECTION 22 TOWNSHIP 17 S RANGE 28 E NMPM.	10. Field and Pool, or Wildcat East Empire Yates 7-R
15. Elevation (Show whether DF, RT, GR, etc.) 3549' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

October 3, 1980 - Spudded well. Ran 120' of 8" PVC casing. Used 25 Sxs. mudjell and 5 Sxs. paper sill. Cemented with 60 Sxs. Class C 4% CaCl.

October 21, 1980 - Plugging Report:  
Drilled to 660'. Twisted off at 460'. Washed down beside drill pipe to 480'. Ran 80 Sxs. Class C 4% CaCl cement. Pulled 200' casing. Ran 90 Sxs. Class C cement. Pulled rest of pipe.

Hole 7 7/8". 170 Sxs. Class C cement to 480'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Donald Craig</u>	TITLE <u>President</u>	DATE <u>11/12/80</u>
APPROVED BY <u>Samy Brooks</u>	TITLE <u>Geologist</u>	DATE <u>3-12-84</u>

CONDITIONS OF APPROVAL, IF ANY: