

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# OIL CONSERVATION DISTRICT

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

DEC 4 1980

Form C-103  
Revised 10-1-

O. C. D.  
ARTESIA, OFFICE

3a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER G 1650 FEET FROM THE North LINE AND 2310 FEET FROM  
THE East LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name  
Gissler AV

9. Well No.  
23

10. Field and Pool, or Wildcat  
Eagle Creek SA

15. Elevation (Show whether DF, RT, GR, etc.)  
3491' GR

12. County  
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

FORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
CUT OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 4:30 PM 11-28-80  
PD 368' Ran 9 joints of 10-3/4" 40.50# K-55 ST&C casing set at 368'. 1-Texas Pattern guide shoe at 368'. Flapper insert float at 331'. Cemented w/250 sacks Class C 4% CaCl. PD 1:00 AM 11-29-80. Cement circulated 35 sacks to pit. WOC 12 hours. Backed off & reduced hole to 9-1/2". Drilled plug and tested to 600 psi, OK.  
PD 1171' Ran 27 joints of 7" 20# ST&C K-55 casing set at 1171'. 1-regular guide shoe at 1171'. Flapper insert float at 1129'. Cemented w/200 sacks Class C Neat, 800 sacks 65-35 Poz, 4% Bentonite, 8# Kolite, 1/4# celloflakes & 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 3:00 PM 11-30-80. Cement did not circulate. WOC 6 hours. Ran Temperature Survey & found top of cement at 745'. Ran 1". Tagged cement at 398'. Spotted 100 sacks Class C 4% CaCl. PD 9:15 PM 11-31-80. WOC 2 hours. Ran 1". Tagged cement at 397'. Spotted 100 sacks Class C 4% CaCl. PD 11:00 PM 11-31-80. WOC 2 hours. Ran 1". Tagged cement at 397'. Spotted 25 sacks Class C 4% CaCl. PD 1:45 AM 12-1-80. WOC 2 hours. Ran 1". Tagged cement at 397'. Spotted 25 sacks Class C 4% CaCl. PD 3:30 AM 12-1-80. WOC 1-1/2 hour. Ran 1". Tagged cement at 397'. Spotted 25 sacks Class C 4% CaCl. PD 4:15 AM 12-1-80. WOC 2 hours. Ran 1". Tagged cement at 397'. Spotted 25 sacks Class C 4% CaCl. PD 6:30 AM 12-1-80. Dumped 1/2 yard of 3/8" pea gravel. WOC 2 hours. Ran 1". Tagged cement at 392'. Spotted 50 sacks Class C 4% CaCl. PD 8:25 AM 12-1-80. WOC 3-1/2 hours. Ran 1". Tagged cement at 390'. Spotted 100 sacks Class C 4% CaCl. PD 12:10 PM 12-1-80. Cement circulated 5 sacks to pits. WOC 18 hrs. NU & tested to 1500 psi, OK. Reduced hole to 6-1/4". Drilled plug & tested to 600 psi, OK.  
I hereby certify that the information above is true and complete to the best of my knowledge and belief. 600 psi, OK.

SIGNED

*Albert R. Hall*

TITLE Engineer

DATE 12/4/80

APPROVED BY

*W.A. Gressett*

TITLE SUPERVISOR, DISTRICT

DATE DEC 6 1980

CONDITIONS OF APPROVAL, IF ANY: