

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.E.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-78

NOV 18 1980

O. C. D.
ARTESIA, OFFICE

50. Indicate Type of Lease State ☒ Free ☐
51. State Oil & Gas Lease No. E-4199
52. Unit Agreement Name ---
53. Name of Lease Name Gulf West Mesa
54. Well No. 1
55. Field and Pool, or Wildcat Undes. Bunker Hill Penrose
56. County Eddy

SUNDARY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR A REQUEST TO CANCEL OR TO REOPEN A WELL RACE TO A DIFFERENT RESERVING.
USE APPLICATION FOR PERMIT TO OPERATE (E-501) FOR SUCH PROPOSALS.

OIL WELL ☒	GAS WELL ☐	OTHER ☐
Name of Operator Read & Stevens, Inc. ✓		
Address of Operator P. O. Box 1518, Roswell, New Mexico 88201		
Location of Well UNIT LETTER M 660 FEET FROM THE South LINE ALL 660 FEET FROM West 13 TOWNSHIP 16-S RANGE 31-E NEPM.		

16. Elevation (Show whether DF, RT, GR, etc.)
4491.8' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

REFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
RE-OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
CONFINEMENT LING OF W. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

Well spudded 8:00 P.M., 10-8-80. Drilled a 12 1/4" hole to TD 1253', 10-10-80. Ran 30 jts., total of 1245', 8 5/8", 23#, S. T. & C. casing, set at 1253'. Cemented w/350 sx. Halliburton Lite cement w/1/2# flocele per sx., followed by 200 sx. "C" Neat cement w/2% CaCl₂ & 1/2# flocele per sx. Cement circulated. Plug down 10:15 P.M., 10-10-80. WOC 18 hrs., pressure tested to 1000#, held okay.

Drilled a 7 7/8" hole to TD 4250' @ 6:00 A.M., 10-17-80. On 10-18-80, ran 106 jts., total of 4242', 4 1/2", 9.5#, K-55, S. T. & C. casing, set @ 4250'. Cemented w/225 sx. Halco Lite cement w/ 3/10 of 1% Halad 4 & 6# salt. Followed w/550 sx. Class "C" cement w/ 3/10 of 1% Halad 4 & 4/10 of 1% CFR2 and 6# salt. Plug down 5:10 P.M., 10-18-80. Bumped plug 2000#, held okay. 10-21-80, TOC 2190', circ. cement.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by Shane Marshall

TITLE Authorized Agent

DATE 11-17-80

APPROVED BY W.A. Gressitt

SUPERVISOR, DISTRICT II

DATE NOV 19 1980

ADDITIONS OF APPROVAL, IF ANY: