

U.S. G.S. 301
July 1968

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other Instructions on reverse side)

Form approved
Budget Project No. 42 R1421
5. LEASE DESIGNATION AND SERIAL NO.

NM-30395

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUMMARY REPORT ABOUT WELLS OR WELLS

(Do not use this form for proposals to drill or to develop or plug back to a different use "APPLICATION FOR PERMIT" for each proposal.)

RECEIVED

JAN 16 1981

O. C. G.
ARTESIA, CALIF.

1. TYPE OF WELL: ☐ GAS ☒ OIL ☐ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. Also space 17 below.)

7. SURFACE

1980' FSL & 1980' FWL

10. PERMIT NO.

12. ELEVATION (Show whether DE, LV, GN, etc.)

3558' GL

7. WELL AGREEMENT NAME

8. FARM OR LEASE NAME

Callaway Federal

9. WELL NO.

3

10. FIELD AND FOOT, OF WIND-CAT

Undes Diamond

Mound Atoka

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 6-16S-28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

1. TEST WATER SHUT-OFF

2. FRACTURE TREAT

3. TEST ON ACH-100

4. TEST WELL

(Other)

5. PULL OR ALTER CASING

6. MULTIPLE COMPLETION

7. ABANDON*

8. CHANGE PLANT

SUBSEQUENT REPORT OF:

9. WATER SHUT-OFF

10. FRACTURE TREATMENT

11. SHOOTING OR ACIDIZING

(Other) Casing

12. REPAIRING WELL

13. ALTERING CASING

14. ABANDONMENT*

X

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

15. WHEN PROCEEDING ON COMPLETION OPERATIONS, particularly at the completion of details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give approximate headings and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 11" hole at 11 P.M., 12-31-80. RU & ran 39 joints & 1 cut joint 8-5/8" 24# K-55 ST&C (1681') set at 1700'. Cement with 750 sacks HCL w/1/2# flocele & 200 sacks Class "C" 2% CaCl₂. Plug down 9:15 A.M., 1-1-81. Circulate cement. WOC 18 hours. Test casing 1500#, 30 min, ok. Drilled plug, float and cement. Start drilling 7-7/8" form 5 A.M., 1-2-81.

JAN 15 1981

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

16. I hereby certify that the foregoing is true and correct.

SIGNED

(Interpreter for blind)

APPROVED BY

CONDITIONS OF APPROVAL

Area Drilling Superintendent DATE 1-13-81

ACCEPTED FOR RECORD

PETER W. CHESTER

JAN 15 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO