

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Jackson Estate BY</u>		Well # <u>12</u>	
Location of Well	Unit <u>E</u>	Section <u>22</u>	Township <u>17</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor	<u>L + M Drilling Co</u>		Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32 #		320	350 SX Circ
9 1/2"	7"	20 #		1150	850 SX Circ
6 1/4"	4 1/2" + 5 1/2"	10.5 # + 15.5 #		1500 ±	Circ

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 9 1/2 Size of Casing 7" Sacks cement required _____

Type of Shoe used Regular Float collar used Insert Btm 3 jts welded yes

TD of hole 1165 Set 1166 Feet of 7 Inch 20 # Grade J-53

New-used csg. @ 1166 with 150 sacks neat cement around shoe

+ 200 sax Thick Set additives + 800 SX 65-35 Pos

Plug down @ 7.30 (AM) (PM) Date 1-10-81

Cement circulated Daewell yes No. of Sacks 50

Cemented by Daewell Witnessed by BLLW

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Last Drilling Break @ 1060