

OIL CONSERVATION DIVISION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Vates Petr Corp</u>		Lease <u>J Lazy J</u>		Well # <u>17</u>	
Location of Well	Unit <u>2310 1650E J</u>	Section <u>22</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>L+m Drlg Co</u>		Type of Equipment <u>Rotary H&amp;AP</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32#		350'	Circ
9 1/2"	7"	20#		1150'	Circ
6 1/4"	4 1/2" + 5 1/2"	10.5# + 15.5#		TD	Circ

Casing Data:

Surface \_\_\_\_\_ joints of 7 inch 20 # Grade \_\_\_\_\_

(Approved) (Rejected)

Inspected by \_\_\_\_\_ Date \_\_\_\_\_

Cementing Program

Size of hole 9 1/2 Size of Casing 7 Sacks cement required \_\_\_\_\_

Type of Shoe used Rc9 Float collar used Insert Btm 3 jts welded yes

TD of hole 1151 Set 1150 Feet of 7 Inch 20 # Grade J-55

New ~~used~~ csg. @ 1150 with 150 sacks neat cement around shoe

+ 450 sax 65/35 Pos \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ 3:45 ( ) (PM) Date 12-12-86

Cement circulated yes No. of Sacks 60

Cemented by Dewell Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_