

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.B.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

DEC 19 1980

O. C. D.
ARTESIA OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation ✓

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER J, 2310 FEET FROM THE South LINE AND 1650 FEET FROM
THE East LINE, SECTION 22 TOWNSHIP 17S RANGE 25E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3527' GR

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

J Lazy J

9. Well No.

17

10. Field and Pool, or Wildcat

Eagle Creek SA

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
WELL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 12:45 PM 12-10-80.

TD 354' Ran 9 joints of 10-3/4" 40.5# K-55 ST&C casing set at 354'. 1-Texas Pattern guide shoe at 354'. Flapper insert float at 313'. Cemented w/250 sacks Class C 4% CaCl. PD 8:45 PM 11-10-80. Circulated 35 sacks to pit. WOC 12 hours. Backed off and reduced hole to 9-1/2". Drilled plug and tested to 600 psi, OK. Resumed drilling.

TD 1150' Ran 28 joints of 7" 20# K-55 ST&C casing set at 1150'. 1-regular pattern guide shoe at 1150'. Flapper insert float at 1110'. Cemented w/450 sacks 65-35 Poz, 4% D-20 Gel, 8# D-42 Kolite, 1/4# D-29 celloflakes, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 4:00 PM 12-11-80. Cement circulated 60 sacks. WOC 18 hours. Nipped up and tested to 1500 psi, OK. Reduced hole to 6-1/4". Drilled plug and tested to 600 psi, OK. Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

Albert R. Hall

TITLE

Engineer

DATE

12-16-80

APPROVED BY

M. Williams

TITLE

OIL AND GAS INSPECTOR

DATE

DEC 20 1980

CONDITIONS OF APPROVAL, IF ANY: