

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Jack L. Hamen</u>		Lease <u>State 16 Corn</u>		Well # <u>1</u>	
Location of Well	Unit <u>6605 1980W N</u>	Section <u>16</u>	Township <u>17</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	?		Type of Equipment <u>Rotary</u> <u>11/20/80</u>		
* Witness					
APPROVED CASING PROGRAM					
Size of Hole <u>24"</u>	Size of Casing <u>20"</u>	Weight Per Foot Casing <u>35#</u>	New or Used <u>1</u>	Depth <u>40'</u>	Sacks Cement <u>Red. mix</u>
<u>17 1/2"</u>	<u>12 3/4"</u>	<u>35#</u>		<u>350'</u>	<u>415 SX Circ</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24#</u>		<u>1700'</u>	<u>1500 SX Circ</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5# 17#</u>		<u>9500'</u>	<u>500 SX</u>
Casing Data:					
Surface joints of <u>8 5/8"</u> inch <u>24</u> # Grade <u>J-55</u>					
(Approved) (Rejected)					
Inspected by <u>M.S.</u> date <u>1/26/81</u>					
Cementing Program					
Size of hole <u>11</u> Size of Casing <u>8 5/8</u> Sacks cement required					
Type of Shoe used <u>Regular</u> Float collar used <u>Float Collar</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1706</u> Set <u>1726</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>1726</u> with <u>400</u> sacks neat cement around shoe					
+ <u>600</u> sax <u>Hawco Lite</u> additives					
Plug down @ <u>8:00</u> (AM) (PM) Date <u>1-28-81</u>					
Cement circulated <u>NO</u> No. of Sacks					
Cemented by <u>Hawco</u> Witnessed by <u>BWW</u>					
Temp. Survey ran @ <u>200</u> (AM) (PM) Date <u>1-28-81</u> top cement @ <u>630</u>					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>Water Sand @ 1125ft</u>					

5:30pm 1. Ran 1" Tagged TOC @ 630'
9:00pm Pumped 185sx C 270cc.
Cement circulated to surface.