FIELD REPORT FOR CEMENTING OF WELLS

| | Operator Marbob Energy Corp | | Lea | Leash Phillips St | | | | Well # 13 | |
|---------------------------------------|--|--|------|-------------------|-----------|-------------|---------|----------------|--|
| | Location of Well 965- | Unit Section FSL P 27 | | Fownsh | ip | enge ع 2 | | County Eddy | |
| | Drilling Contractor Yucca Drlg (o Rotary | | | | | | | | |
| | *' | 1 1 | | | | | | | |
| | Size of Hole | Size of Casing | 1 | ight Per Foot | Nev | v or Used | l Depth | Sacks Cemen | |
| | <u> </u> | 8 5/8 " | | z4# | | | 140' | Circ | |
| * | 7 1/8 ' | 4 '/z '' | | 10.50# | | - | 1050' | 35054 Gire | |
| 1 | Cacing Datas | | | | | <u></u> | | 1 | |
| | Casing Data: | | | | | | | | |
| | | rfacejoints ofinch# Grade (Approved) (Rejected) | | | | | | | |
| • | Inspected by | | date | | | | | | |
| | Cementing Program | | | | | | | | |
| | Size of hole 71/2 Size of Casing 41/2 Sacks coment required | | | | | | | | |
| | Type of Shoe used Bit Float collar used INSert Btm 3 its welded yes | | | | | | | | |
| | TD of hole <u>920</u> Set 930 Feet of $\frac{4}{2}$ Inch 10.5 = Grade <u>J-55</u> New-used csg. @ <u>930</u> with <u>200</u> sacks near coment around shoe | | | | | | | | |
| | | | | | | | | | |
| | + <u>/00</u> _sax | والمتحدث بالمكافين فالمحمد المحمد | | | | | | | |
| | Plug down @ 12:30 (AM) (22) Date 12-23-80 | | | | | | | | |
| | Cement circulated <u>No</u> No. of Sacks | | | | | | | | |
| | | Henco | | | | | | | |
| | | ran @ (AM) (| | | | top c | ement @ | | |
| | Casing test @(AM) (FM) Date | | | | | | | | |
| | Method UsedWitnessed by | | | | | | | | |
| Checked for shut off @ (AM) (PM) Date | | | | | | | | | |
| | ethod usedWitnessed by | | | | | | | | |
| | Remarks: | | | | | | | | |
| | | | | | | | | | |
| | New York and the Annual State of the Annual S | | | | , | | | | |
| | | | | | | | | | |
| | | | | | | | | | |