

DISTRIBUTION		
SANTA FE		
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Effective 1-1-85

FEB 20 1981

O. C. D.

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-1111	

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Collier Energy, Inc. ✓
3. Address of Operator P.O. Box 798 Artesia, New Mexico 88210
4. Location of Well UNIT LETTER <u>A</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>17S</u> RANGE <u>28E</u> NMPM.

7. Unit Agreement Name
8. Farm or Lease Name State B-1111, Tr. 2
9. Well No. #19
10. Field and Pool, or Wildcat East Empire Yates 7-R
12. County Eddy

15. Elevation (Show whether DF, RT, GR, etc.) 3648 GL
--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

January 30, 1981: Spudded well. Ran 200' 8" P.V.C. Cemented with 70 SXS Class C 4% CaCl. Circulated to surface. WOC 24 hrs.

January 31, 1981: Drilled with 7 7/8" bit to T.D. 915'. Ran 910' 4 1/2", 9.5# casing with Float shoe and 3 centralizers. Cemented with 300 SXS Class C Cement. Circulated 10 SXS to Pit. WOC 24 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald Cray TITLE President DATE 2/17/81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE FEB 25 1981

CONDITIONS OF APPROVAL, IF ANY: