

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collier Energy Inc</u>		Lease <u>State B-1111 Tr 2</u>		Well # <u>21</u>	
Location of Well	Unit <u>330N 990E A</u>	Section <u>22</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor	<u>Yucca Drllg Co</u>		Type of Equipment <u>Rotary</u>		
*Witness					
<u>APPROVED CASING PROGRAM</u>					
Size of Hole <u>12 1/4"</u>	Size of Casing <u>8" PBC</u>	Weight Per Foot	New or Used	Depth <u>160'</u>	Sacks Cement <u>70.54% ca circ</u>
* <u>7 7/8</u>	<u>4 1/2</u>	<u>95#</u>		<u>700'</u>	<u>250 SX - Circ</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 7/8" Size of Casing 4 1/2" Sacks cement required _____

Type of Shoe used guide shoe Float collar used _____ Btm 3 jts welded No

TD of hole 970' Set 961' Feet of 4 1/2" Inch 9.5 # Grade J-55

(New) used csg. @ 961' with 300 sacks neat cement around shoe

+ _____ sac _____ additives _____

Plug down @ 10:00 (AM) (PM) PM Date 2/4/81

Cement circulated Yes No. of Sacks 12

Cemented by Denton cementing Witnessed by Michael Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers @ 941' - 901' - 861' Wtr @ 875' slight show