

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Latch Operations</u>		Lease <u>Spurck</u>		Well # <u>7</u>	
Location of Well	Unit <u>1650</u> <u>330E</u>	Section <u>24</u>	Township <u>17E</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>Plains Drlg Corp</u>		Type of Equipment <u>CT</u>		

*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12	10 3/4	40		441	2009 Cms
10	8 5/8	26		600	2509 Cms

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 15 1/2 Size of Casing 10 3/4 Sacks cement required 350 sacks + 5.5 yds.

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 456 Set 456 Feet of 10 3/4 Inch 40.5 # Grade J or k - ss ?

New-used csg. @ 456 with 350 sacks neat cement around shoe
+ _____ sack _____ additives _____

Plug down @ 11:00 (AM) (PM) Date 9/2/81

Cement circulated NO No. of Sacks —

Cemented by DENTON Witnessed by LARRY BROOKS

Temp. Survey ran @ _____ (AM) (PM) Date 9/3/81 top cement @ 220' by sinker bar

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Redmixed to surface w/ 5 1/2 yards of cnt.

Fluid level 200'?