

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well well

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 330 FSL & 2310 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)	<input type="checkbox"/>		<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled a 15" hole at 4:00 PM 1-21-81.
353' Ran 9 joints of 10-3/4" 40.50# K-55 ST&C casing set at 353'. 1-Notched guide shoe at 353'. Flapper insert float at 313'. Cemented w/250 sacks Class "C" 2% CaCl. PD 2:30 AM 1-22-81. Bumped plug to 500 psi, released pressure & float held okay. Cement circulated 40 sacks to pit. Compressive strength of cement in 10-3/4" casing - 1850 psi in 12 hours. WOC 12 hours. Reduced hole to 9-1/2". Drilled plug and resumed drilling.
1187' Ran 27 joints of 7" 20# K-55 ST&C casing set at 1187'. 1-notched guide shoe at 1187'. Flapper insert float at 1147'. Cemented w/400 sacks 65-35 Poz, 4% Bentonite, 8# Kolite, 3% CaCl and 1/4# celloflakes. Tailed in w/150 sacks Class "C" 2% CaCl. PD 7:00 PM 1-23-81. Bumped plug to 900 psi, released pressure and float held okay. Cement circulated 60 sacks to pit. WOC 18 hours. Nippled up and tested to 1500#, OK. Reduced hole to 6-1/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Peter W. Chester TITLE Engineering Secretary DATE Jan. 28, 1981APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANYACCEPTED FOR RECORD
(This space for Federal or State office use)
PETER W. CHESTER

JAN 30 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE
NM 0219603

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal BW

9. WELL NO.
10

10. FIELD OR WILDCAT NAME
Eagle Creek SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit 0-Sec 22-T17S-R25E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW OF, KDB, AND WD)
3524' CR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)