Submit 3 Copies To Appropriate District Office <u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 South First, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of I Energy, Minerals a OIL CONSERV 1220 South Santa Fe	and Natu ATION 1 St. Fran	ral Resources DIVISION ncis Dr.	SI	30-01 ate Type of TATE	Form C Revised March 25 15-23608 Lease FEE X s Lease No.	-	
SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OB PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM CLOS) FOR SUCH PROPOSALS.) 1 Type of Well: Oil Well Gas Well Other Infection BHWFU (Formerly Dartmouth #1)								
Oil Well Gas Well 2 Name of Operator	Other Int		ECK, SUZZ	8. Well			#1)	
Read & Stevens, Inc.				ੋਂ 15				
3 Address of Operator			u / I	9. Pool name or Wildcat				
P. O. Box 1518 Roswell, New Mexico 88202 7 5 Bunker Hill Penrose								
		12	241919191710					
Unit Letter P : 66	0feet from the		line and	660	_feet from t	he East	_line	
Section 14	Township 16			NMPM	C	County Eddy		
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4,393.1 GL								
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data								
				BSEQUE	NT REPO	DRT OF:		
PERFORM REMEDIAL WORK D	UG AND ABANDON	X	REMEDIAL WO	RK	A []	LTERING CASI	٧G	
	IANGE PLANS		COMMENCE D	RILLING OPN		LUG AND		
	ULTIPLE MPLETION		CASING TEST CEMENT JOB	AND				
OTHER:			OTHER:		<u>.</u>			

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Read & Stevens proposes to plug and abandon the subject well by placing a Set as supluy CIBP at 3,500' and capping w/ 35' of cmt. This will abandon existing Penrose perforations 3,602'-3,622'. The 4 1/2" csg will then be cut and pulled from the @ 2450'-→ approximate top of cmt at 2,060' (TOC by TS). A 100' cmt plug will be placed 50' in and 50' out of the csg stub and tagged. A 100' cmt plug will be placed across the top of the salt and 50' out and 50' in the base of the 8 5/8" surface csg which is located at 1,236', and tagged. A 100' cmt plug will be set with the base at 350' to protect fresh water, and after the wellhead is cut off a 60' surface plug will be installed with a dry hole marker being erected.

TA 9

Notify OCD 24 hrs. prior to any work done

I hereby certify that the information above is true and co	mplete to the best of my knowledge and belief.	
SIGNATURE	TITLE Operations Manager	DATE 7-29-02
Type or print name John C. Maxey, Jr.	Tel	ephone No. 505/622/3770
This space for State use)	1. OL Den D	AUG 12 2062
APPPROVED BY	TITLE THE SALE	DATE
Conditions of approval, if any:	, , , , , , , , , , , , , , , , , , ,	