

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other ☐

2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 330' FSL & 1650' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1500' WIH w/Steel Strip gun on wireline & perforated in 2 stages as follows:  
1st stage: 1320-1443' w/12 .50" holes as follows: 1320, 25, 32, 40-1/2, 47, 54, 58, 87, 1400, 12, 35 & 43'. Ran tubing & packer to acidize & ball out 1st stage of perforations. Pulled tubing & packer. 2nd stage: WIH w/Steel Strip gun on wireline & perforated 1272-1437-1/2' w/16 .50" holes as follows: 1272, 86, 1306, 22, 27, 29-1/2, 35, 43, 50, 56, 63-1/2, 79, 89, 1402, 33 & 37-1/2'. Treated perforations w/2000 gallons 15% regular acid, 60000 gallons gelled 1% KCL water, 90000# sand (80000# 20-40 sand & 10000# 100 mesh) 2 drums Unichem scale inhibitor.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Peter W. Chester TITLE Secretary DATE Feb. 11, 1981

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

FEB 12 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

NM-0219603-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal BW

9. WELL NO.

11

ARTESIA OFFICE

10. FIELD OR WILDCAT NAME  
Eagle Creek SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit N, Sec. 22-T17S-R25E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3536' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
FEB 12 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO