

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Yates Petroleum Corp		Lease Gissler AV		Well # 25	
Location of Well	Unit 23105 1650W K	Section 23	Township 17	Range 25	County Eddy
Drilling Contractor Le Rue Drilling Co			Type of Equipment Rotary- Soon after approval		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32 #		350'	200 SX Circ
9 7/8"	7"	20 #		1150'	700 SX Circ
6 1/4"	4 1/2" + 5 1/2"	10.5# + 15.5#		1500'	150 SX

Casing Data:

Surface _____ joints of _____ inch _____ # Grade K-SS

(Approved) (Rejected)

Inspected by Bww date _____

Cementing Program

Size of hole 9 7/8 Size of Casing 7" Sacks cement required _____

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Yes

TD of hole 1190 Set 1192 Feet of 7 Inch 20 # Grade K-SS

New-used csg. @ 1192 with 150 sacks neat cement around shoe

+ 200 Class C sax 800 65/35 Ps mix additives 3% CC + 5# Gilsenite

Plug down @ 3:00 (AM) (PM) Date 2-6-81

Cement circulated NO No. of Sacks None

Cemented by Dowell Witnessed by Bww

Temp. Survey ran @ 9:00 (AM) (PM) Date 2-6-81 top cement @ 620

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Lost Circ e 746' Btm Drlg Break e 1081'

1st stage Tagged e 403' Pumped 180 SX Cement

2nd stage Tagged e 372' Pumped 230 SX Cement

3rd stage Tagged e 372' Pumped 50 SX Cement

4th stage Tagged e 372' Pumped 50 SX Cement

5th stage Tagged e 372' Pumped 75 SX Cement

6th stage Tagged e 372' Pumped 65 SX Cement - Circ 5 SX to the pit

Total 650 SXs