

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Zumwalt PT</u>		Well # <u>1</u>	
Location of Well	Unit <u>330N 2310W C</u>	Section <u>31</u>	Township <u>16</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Artesia Fishing Tool</u>		Type of Equipment <u>Rotary 1-30-81</u>			
* Witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 3/4"</u>	<u>32#</u>		<u>400'</u>	<u>Circ</u>
* <u>9 1/2"</u>	<u>7"</u>	<u>20#</u>		<u>1250'</u>	<u>Circ</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5#</u>		<u>2200'</u>	
Casing Data:					
Surface _____ joints of <u>7</u> inch <u>20</u> # Grade <u>K-SS</u>					
(Approved) (Rejected)					
Inspected by <u>M.S.</u> date <u>2/2/81</u>					
Cementing Program					
Size of hole <u>9 1/4"</u> Size of Casing <u>7"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1157'</u> Set <u>1156'</u> Feet of <u>7"</u> Inch <u>20</u> # Grade <u>K-SS</u>					
(New-used) csg. @ <u>1156'</u> with <u>150</u> 2% sacks neat cement around shoe					
+ <u>400</u> sax <u>5/35</u> poz. additives <u>4% gel, 8# Kelite, 1/4# cellophane, 3% occ.</u>					
Plug down @ <u>7845</u> (AM) (PM) Date <u>2/2/81</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>45</u>					
Cemented by <u>Dowell</u> Witnessed by <u>Mike Stillfield</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
No centralizers					
Last day break @ 1066'					