

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Yates Drilling Company ✓
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1995' FNL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Production Casing			

5. LEASE
NM 32585
6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
7. UNIT AGREEMENT NAME
JUL 13 1981
8. FARM OR LEASE NAME
Logan Draw Yeso OT Fed. O. C. D.
9. WELL NO.
1-
ARTESIA, OFFICE
10. FIELD OR WILDCAT NAME
Wildcat Yeso
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit F, Sec. 20-T17S-R27E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3374' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3111'. Ran 78 jts. of 4-1/2" 9.5# (3114.93') of casing set at 3111'. Float shoe at 3111'. Used 4 centralizers. Cemented w/250 sacks Class "C" 2% CaCl. PD 12:00 noon 5-13-81. Bumped plug to 500 psi, released pressure and float held okay. Ran Temperature Survey and found top of cement at 410'. Waiting on completion unit. WIH w/strip gun and perforated 2805-2926' w/11 .42" holes as follows: 2805, 11, 17, 26, 33, 65, 79, 89, 97, 2902, 2926'. Spotted 2000 gal. 15% HCL acid over perms. Perforated 15 holes 2799-2928' as follows: 2799, 2803, 2809, 2815, 2822, 2824, 2828, 2835, 2862, 2873, 2887, 2894, 2900, 2909, 2928'. Frac'd with 2000 gallons 15% HCL followed with 60000 gal. gelled wtr., 90000# sand (10000# 100 mesh and 80000# 20-40 sand). Pumping back load.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. Chapman TITLE Engineering Sect. DATE 7-6-81

ACCEPTED FOR RECORD (This space for Federal or State office use)

ROGER A. CHAPMAN

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

JUL 7 1981

U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

See Instructions on Reverse Side

RECEIVED
JUL - 7 1981
U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO