

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Albuquerque, NM 88210

SUBMIT IN TRIP DATE  
(Other instructions on reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

Yates Drilling Company

ADDRESS OF OPERATOR

105 South 4th Street, Artesia, New Mexico 88201

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

1980' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3374' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM-32585

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Logan Draw Yeso OT Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Logan Draw San Andres

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Section 20-17S-27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was originally drilled to 3111'. Perforations from 2862'-2928' were squeezed below a permanent retainer at 2848' w/ 150 sx. of cement. Perforations 2799'-2835' were squeezed below a permanent retainer at 2768' w/ 100 sx. cement. The well has the remaining perforations open 2711'-15' and 1757'-1839'.

We propose to plug and abandon the well as follows:

1. Pull rods, pump and tubing
2. Trip in hole with tubing and bit to permanent bridge plug at 1875'
3. Pick-up power swivel and drill out bridge plug
4. Lower tubing and tag plug back TD at approx. 2768'
5. Circulate hole w/ 25#/barrel of SW gel
6. Trip in hole w/ tbg. and retainer, set at 2680'
7. Squeeze perforations 2711'-15' w/ 25 sx. Class "C" cement
8. Sting out of retainer and spot 5 sx. Class "C" cement on top
9. Pull tbg.
10. Trip in hole w/ tbg. and second retainer, set at 1730'
11. Squeeze perforations 1757'-1839' w/ 50 sx. Class "C" cement
12. Sting out of retainer and spot 25 sx. Class "C" cement on top
13. Pull tbg. to 362'
14. Spot 10 sx. Class "C" cement 262'-362'
15. Pull tbg. to 100'
16. Spot 10 sx. Class "C" cement 0'-100'
17. Erect regulation marker, clean and level location.

I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 5-14-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 5-21-87

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side