

# WELL DATA SHEET

FIELD Diamond Mount  
 LEASE AND WELL No. Husky Federal Well No. 1  
 LOCATION 660' FNL, 1980' FEL, Sec. 17, T-16-S, R-27-E  
 COUNTY AND STATE Eddy County, New Mexico  
 STATUS Shut-in  
(Pumping, Flowing, gas lift, etc.)

TD 8640' PBTD 2497' GR 3490' KB 3508'

SURFACE CASING 13-3/8" 40 lb./ft. set at 395'  
Cemented w/ 422 sx. Class "C". TOC Surface.

INTERMEDIATE CASING 8-5/8" 24 lb./ft. set at 1500'  
Cemented w/ 700 sx. Class "C". TOC Surface.

SURFACE CASING: 5-1/2" 15.5 and 17 lb./ft. set at 8640'  
Cemented with 1315 sx. Class "C" in two stages.  
Perf. squeeze holes at 2550'. Cemented w/ 400 sx.  
Class "C". TOC 1200'.

TUBING 2-3/8"

PUMPING UNIT None

PRESENT COMPLETION (Formation and Interval)   
2066'-2130' and 2465'-2476' (2 JSPF - 36 holes)

HISTORY: Drilled by Husky in May, 1981. 8/87: Attempted recompletion to Gravgburg -  
unsuccessful. Proposed to abandon by setting CIBP at ±2040' w/ 35' cement plug.  
Load hole w/ salt gel. Spot 100' plug at 1450' - 1550'. Spot 100' plug 450' - 350'.  
Set 50' surface plug.

PREPARED BY: Eric M. Pringle DATE: August 11, 1987

\*50' plug

\*100' plug

395'

\*100' plug

1500'

\*35' plug

\*CIBP 2040'  
2066'

2476'

CIBP 5820'

5868'  
5873'

CIBP 7800'  
7910'-  
7925'

CIBP 8200'  
8265'  
8281'

8640'

TD 8640'

\* Proposed